



AXLOC-VW2

INTERFACE KIT



INTERFACE FEATURES

- Designed to provide (2) channels of low-level audio output from the factory system.
- Allows for the installation of an amplifier for speakers or subwoofers.
- Gain Controller included to adjust the overall output.
- 12v-500mA remote wire activated with signal sense.
- 55-watts per channel.

Note: A single pole double throw (SPDT) relay is recommended when installing multiple amplifiers.

INTERFACE COMPONENTS

- AXLOC-VW2 Wiring Harness
- Gain Controller
- 12v-500mA Remote Wire
- Auxiliary Cable

Volkswagen LOC (Line Output Converter) AXLOC-VW2 (for Non-Amplified Vehicles) 2016-Up

Visit AxxessInterfaces.com for more detailed information about the product and up-to-date vehicle specific applications.

APPLICATIONS

Volkswagon

Beetle	2016-Up
Golf	2015-Up
Jetta	2016-Up
Passat	2016-Up
Tiguan	2016-Up

For dash disassembly instructions, refer to metraonline.com. Enter the year, make, and model of the vehicle in the **Vehicle Fit Guide** for **Radio Install Kits**.

SALES 386-257-2956

REV. 8/1/22

What Fits My Vehicle? See the [Vehicle Fit Guide](http://VehicleFitGuide.com) at AxxessInterfaces.com


© COPYRIGHT 2022 METRA ELECTRONICS CORPORATION