



24V

WARNING!

USE ONLY IN VEHICLES WITH A 24 VOLT
NEGATIVE GROUND

ATTENZIONE:

Questo amplificatore GLADEN ONE è una variante a 24V pertanto può essere utilizzato solo in veicoli con alimentazione a 24V.

Per quanto riguarda le specifiche tecniche fare riferimento alla tabella riportata di seguito.

Per tutte le altre indicazioni di installazione e regolazione fare riferimento al manuale d'uso allegato.

ACHTUNG! WARNHINWEISE:

Dieser GLADEN ONE Verstärker darf nur in Fahrzeugen mit 24V Bordspannung betrieben werden!

In der Tabelle unterhalb sind alle wichtigen technischen Spezifikationen aufgelistet.

Alle Hinweise zum Einbau entnehmen Sie bitte der angefügten Einbauanleitung!

WARNING! CAUTION:

This GLADEN ONE amplifier is a 24V version, therefore it can only be used in vehicles with 24V power supply.

As for the technical specifications, please refer to the table below.

For all other instructions of installation and adjustment, please refer to the user's manual attached.

TECHNICAL SPECIFICATIONS

Amplifier	ONE 130.4 24V
Power supply voltage	20 - 32V
DC-DC converter typology	Unregulated – Push Pull
External fuse	2 x 20A
Autosense power-on	in High Level mode only
Overall efficiency	>60%
Stereo power RMS @4Ω	130W x 4
Stereo power RMS @2Ω	175W x 4
Bridge power RMS @4Ω	350W x 2
Low level + High level input sensitivity range	0.35 ÷ 16V
Onboard crossover filter configuration	OFF - LP - HP
LP or HP filter frequency range	20 ÷ 225Hz
LP & HP filter slope	12 dB/Oct
Low level & High level input	RCA
Remote control (optional)	Modular jack
Dimensions	310x200x50mm
Weight	2.7Kg
Color and finishing	Black powder coating