

WHITE / AMBER  
POSITION LIGHT



## SIBERIA DRC LED BAR *E-APPROVED*



PART NO.	809196	809197	809198	809199
VOLTAGE	10-40V DC	10-40V DC	10-40V DC	10-40V DC
CONSUMPTION	91W	284W	394W	487W
THEORETICAL LUMEN	16000	24000	32000	38400
ACTUAL LUMEN	6161	12663	15800	18900
1 LUX @	415m	543m	557m	573m
IP-CLASS	IP67/IP69K	IP67/IP69K	IP67/IP69K	IP67/IP69K
BEAM PATTERN	Combo	Combo	Combo	Combo
POSITION LIGHT	Yes, white and amber	Yes, white and amber	Yes, white and amber	Yes, white and amber
CONNECTION	DT-4	Cable	Cable	Cable
CABLE LENGTH	500mm	2500mm	2500mm	2500mm
MATERIAL HOUSING	Aluminium	Aluminium	Aluminium	Aluminium
MATERIAL LENS	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate
LENGTH	566,33mm	823,16mm	1078,4mm	1281,11mm
DEPTH	71,6mm	71,6mm	71,6mm	71,6mm
HEIGHT	76mm	76mm	76mm	76mm
HEIGHT INCLUDING BRACKET	89mm	89mm	89mm	89mm
OPERATING TEMPERATURE	-20°C · +45°C	-20°C · +45°C	-20°C · +45°C	-20°C · +45°C
E-APPROVED	ECE R7, R112	No	No	No
REF	40	-	-	-
EMC-CERTIFICATE	ECE R10	ECE R10	ECE R10	ECE R10